

Dencrete

HF (9 mm)

Recommended for areas, which are subject to extremely heavy mechanical or high chemical charges, with hygienic demands, such as dairies, bakeries, breweries, slaughter houses, smokehouses, ovens and cold stores, and generally in the food industry, where steam cleaning is required.

Benefits

- Excellent chemical resistance
- Resist 130°C water temperatures
- High abrasion resistance
- Seamless and hygienic finish
- Easy to clean and sterilise
- Low maintenance cost
- Anti slip finish if required
- Low odour during installation

Scope of use

- Wet and dry process areas
- Dairies
- Bakeries
- Breweries
- Slaughter houses



For more colors please see separate color chart.





Dencrete **HF** (9 mm)

Appearance

Dencrete[™] HF is a coloured smooth floor with white fleck, which is exposed as the surface is trafficked.

Life Expectancy

15 - 25 years.

Application

To provide a heavy duty floor finish with exceptional temperature and chemical resistance. Typical uses are wet and dry process areas with hot liquid spillage, hot water cleaning, heavy traffic, impact and chemical exposure.

Application conditions

Temperature 10°C to 30°C., best 15 to 25°C., max. moisture content in the concrete subfloor 5% by weight.

Temperature Resistance

Dencrete™ HF is resistant to temperature cycles up to 130°C wet heat. Extended periods at these temperatures and above will make material susceptible to chemical attack and abrasion wear.

Colours

See separate color chart.







Properties

Fully cured at 20°C Applied thickness Water Permeability

Hardn<u>ess</u>

Compressive strength Reaction to fire Bond strength Temperature resistance Thermal expansion coefficient

Abrasion resistance Thermal conductivity

Slip resistance **Food Contact**

Value

3 days 9 mm

Nil - Karsten test (impermeable)

SHORE D 90

55 MPa

 $B_{fl} - S_1$

> 1.5 MPa

Up to 130°C at 9 mm

< 25 ppm

50 mg / 1000 cycles (Taber Abrader)

< 1.5 W/m·K

R9 - R13

No contamination

DenCoat™

E-mail: info@dencoat.com · Website: www.dencoat.com

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsability on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to the technological progress or further developments. The customer is not released from the obligation to conduct carefull inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out by only qualified experts in the selection and testing of incoming goods. sole responsability of a customer. Please contact DenCoat for the latest version. All our documents, offers, ect. are in association with our general sales, delivery and application conditions.

