

Denpox Industry (4-6 mm)

A three pack, solvent free epoxy resin based flooring material. Denpox Industry 4 - 6 mm is ideal for areas, with high hygienic demands. It is recommended for industrial environments, which are subject to heavy mechanical and chemical wear. The floor is easy to maintain, and is used for industrial production, chemical industry, slaughter houses and other food industries, breweries, etc.

Benefits

- Non slip finish if required
- High impact resistance
- Seamless and hygienic finish
- Very good chemical resistance
- Easy to clean and sterilise
- Low maintenance cost
- Attractive appearance
- High abrasion resistance
- Solvent free; low odour

Scope of use

- Food industries
- Chemical industry
- Breweries
- Slaughter houses



For more colors please see separate color chart.





Appearance

Denpox Industry is a multicoloured floor which can be produced with a non slip finish as required.

Life Expectancy

10 - 20 years.

Application

To provide a medium to heavy duty, easy to clean, chemical resistant flooring. The non slip finish can be adjusted to clients need. Typical uses are process, manufacturing, packaging and warehousing areas subjected to heavy wear and pallet truck traffic.

Application conditions

Temperature 10°C to 30°C, best 15 to 25°C, max. moisture content in the concrete subfloor 5% by weight.

Temperature Resistance

Denpox Industry is resistant to temperature cycles up to 70°C. Extended periods at these temperatures and above will make material susceptible to chemical attack and abrasion wear.

Colours

See separate color chart.







Properties

Fully cured at 20°C Applied thickness Water Permeability

Hardness

Compressive strength Reaction to fire Bond strength

Temperature resistance
Thermal expansion coefficient

Abrasion resistance

Thermal conductivity
Slip resistance

Food Contact

Value

7 days 4 - 6 mm

Nil – Karsten test (impermeable)

SHORE D 80

60 MPa B₁ - s₁

J₁ J₁

>1.5 MPa

Up to 70°C at 4 mm

<38 ppm

50 mg / 1000 cycles (Taber Abrader)

< 0,6 W/m·K

R9 - R13

No contamination

DenCoat™

E-mail: info@dencoat.com · Website: www.dencoat.com

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether expressed or -implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or -further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out by only qualified experts in the sole responsibility of a customer. Please contact DenCoat for the latest version. All our documents, offers, ect. are in association with our general sales-, delivery- and application conditions.