

Denpox™ Aqua Hardener

Aqueous Epoxy Hardener

DESCRIPTION

Denpox™ Aqua Hardener is a water borne hardener for epoxy paints.

FEATURES AND BENEFITS

- Water borne
- Excellent compatibility
- Excellent bond to substrate
- Stable emulsion

FIELDS OF APPLICATION

Denpox™ Aqua Hardener is typically used for colored epoxy paints.

PACKAGING

Denpox™ Aqua Hardener is supplied in 12.5 kg units.

SHELF LIFE

Minimum 12 months stored in original containers under dry conditions at a temperature between 15-20°C. Do not expose to direct sunlight.

Technical data for Liquid material

Property	Method	Values
A.E.W.		308 g/eq
Density		1,01 g/ml
Viscosity		Non-newtonien
Solid content		36%
Gardner colour		< 3

DenCoat™ E-mail: info@dencoat.com · Website: www.dencoat.com

This information and all further technical advice is based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to the technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out by only qualified experts in the sole responsibility of a customer. Please contact DenCoat for the latest version. All our documents, offers, ect. are in association with our general sales, delivery and application conditions.